

BRILLIANCE SUPERWAX

Description

BRILLIANCE SUPERWAX is a paste-like care agent in a very mild solution that is based on valuable and natural raw materials. It is used for all sealed and oiled/waxed parquet and wood block paving floors, linoleum, cork linoleum and stone block floors, as well as other solvent-resistant surfaces.

Certificates / approvals



Giscode: Ö60

Instructions for use

BRILLIANCE SUPERWAX is used on all suitable floors that are clean and dry. Usage instructions:

- Apply with a cloth or spatula, manually or mechanically. It is important to apply this product in very thin layers. Polish manually or mechanically once the wax layer has dried after about 20-30 min at 23°C / 50% humidity
- Process as warm wax. To do this, the wax is either placed in a water bath or heated up to a temperature of approx. 80°C in a heating unit. It is applied by spraying and, at the same time, polishing with the monodisc unit with a white or beige pad attached; it is polished again with the machine approx. 20-30 min after the wax is applied

Basic cleaning

Basic cleaning with BRILLIANCE CLEANER L91 KH-DILUTION is always necessary if the floor is dirty. To this end, the BRILLIANCE CLEANER L91 KH-DILUTION IS APPLIED with a mop or a spray, then polished and the dirt is mopped up with absorbent cloths.

Usage

Depending on the surface and work method:
approx. 10 ml/m² 4000 sf/gal

Storage / transport

Ensure cool, dry and frost proof conditions during transport and storage; it can be stored in the unopened original packaging for at least 24 months.

Important information

The BRILLIANCE SUPERWAX has a high wax content and therefore creates relatively smooth floors. This may be preferred or simply tolerated. However, in some cases, a smooth surface of this kind is not appropriate, especially if it is used by vulnerable people or in most public buildings. Unless the flooring has only been impregnated and there is a good intact sealing layer, we recommend our non-slip water-based care agent BRILLIANCE EVERCLEAR.

Storage and transport

If transported and stored in cool and dry conditions, the unopened original packaging can be stored for at least 24 months.

General information

Please read the instructions for use carefully before using the product. This Berger-Seidle product may only be used by persons who are qualified to lay parquet flooring; these instructions are written for these persons. The tasks must be carried out in compliance with the rules of the trade, the state of the art and the valid norms and regulations of the country in which the product is used. The specifications of the DIN 18356 'Parquet work and wood block paving work', DIN 18365 'Flooring work', information sheets of the TKB, the BEB, the CTA and the BVPF Federal Association of Parquet & Flooring Technology must be observed. The customer must be informed about the cleaning and maintenance instructions for the product. Any use that does not comply with the Berger-Seidle application scope is deemed improper. The person using the product is solely responsible for incorrect use and non-observance of the information in these instructions; this will invalidate the liability and warranty of the manufacturer. The application guidelines must be observed before using the product.

References

The following sections of our information pages are integral parts of this information sheet:

- General information about how to use parquet sealing products
- Cleaning and care of the sealed/oiled floor
- Labelling and safety information (safety data sheet)

* If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.