

AQUASEAL PAFUKIPOWDER COLOR

Description

AQUASEAL PAFUKIPOWDER is a wood-colored solvent-free product based on dispersion powder for the preparation of wood filler or joint putty. AQUASEAL PAFUKIPOWDER is mixed with water in order to achieve the required flow properties. The filling compound is used for filling joints, cracks etc. within all kinds of wooden substrates, e.g. parquet, hardwood flooring etc.

Certificates / Approvals



Giscode: W1
ATFA: Member
NWFA: Member
MFMA: Member

Color shades

AQUASEAL PAFUKIPOWDER is available in the following color shades:

light oak	XZ03-8067-0A0
beech/red oak	XZ03-8072-0A0
maple/ash/pine	XZ03-8075-0A0
wenge/smoked oak	XZ03-80S6-0A0
azobe/teak	XZ03-8076-0A0
jarrah/red eucalyptus/brazilian cherry	XZ03-C062-0A0
white	XZ03-10A8-0A0
black	XZ03-4060-0A0

Application

AQUASEAL PAFUKIPOWDER is mixed with water until the application consistency is achieved. That means that, depending on the color, 2.2 lbs of AQUASEAL PAFUKIPOWDER mixed with the corresponding quantity of water will result in approx. 37.2 – 40.6 us fl oz of liquid mixture, i.e., 11.02 lbs of powder + 118.3 us fl oz of water = 1.45 us fl gal wood filler. If necessary (e.g. for very absorbent substrates), the quantity of water can be increased. Stir well. As soon as a homogenous filler compound suitable for troweling is ready, the product is applied to the complete surface using a trowel in the same way as conventional fillers. Filler mixtures containing too much water will settle down in the gaps during the drying process. In case the mixture contains too much powder, the filler may be torn out of the gap during the next sanding procedure. Large joints must be closed with pieces of wood and joints containing wax must be cleaned prior to the application of the filler compound.

The AQUASEAL PAFUKIPOWDER filler compound should be applied quickly without leaving any residues as they will dry immediately. The pot life of the mixture is approx. 45 minutes. Afterwards the material starts thickening. Final sanding of the floor is carefully effected after the floor is sufficiently dry safeguarding that no residues of the product remain on the floor. A floor treated with AQUASEAL PAFUKIPOWDER can be

recoated with any kind of our finishes. AQUASEAL PAFUKIPOWDER cannot be mixed with sanding dust.

AQUASEAL PAFUKIPOWDER is also used as color-/hardener component in combination with AQUASEAL PAK-STOP. Please refer to the relevant Technical Data Sheet of AQUASEAL PAK-STOP.

Drying

At 73.4°F/50% rel. humidity and standard trowel application of a floor with small joints only: sandable after approx. 20-30 minutes. Large joints and cavities may delay drying considerably. Do not screen before the surface is sufficiently dry.

Consumption

Depending on substrate and working method:

1 trowel coat:
approx. 0.13-0.2 oz/ sq ft resp. approx. 694-1020 sq. ft/gal

In case of large joints and cavities, consumption may be increased considerably.

Storage / transport

Shelf life of original unopened packing 60 months min. provided that material is transported and stored at a cool and dry place protected from freezing.

Safety Precautions

Do not use for sputtering or spraying. Keep out of reach of children. Residual quantities should not be poured into sewage water drains, but disposed of in compliance with local, state, and federal regulations.

Description of first aid measures

If medical advice is needed, have product container or label at hand.

24-hour emergency number in side USA: +1 49 700 24112112

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

AQUASEAL PAFUKIPOWDER COLOR

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

Manufacturer's Recommendations

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußboden-technik must be observed. The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

Cross reference

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing products
- Cleaning and maintenance of finished/oiled floors
- Identification and safety instructions (MSDS)

* If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.