

BRILLIANCE OILCARE

BRILLIANCE OilCARE is an oil/wax care product for surfaces treated with our CLASSIC 100PROOIL or CLASSIC BASEOIL. It is applied after cleaning, works like a back impregnation, freshens up the surface optically too, and ensures an appropriate care and protection. The product is made of refined vegetable oils and waxes.

Certificates / Approvals



Giscode: Ö60
ATFA: Compliant
NWFA: Compliant
MFMA: Compliant

Specifications

Components:	oil/wax
Clarity:	translucent, dries clear
Scent:	lemon
Packaging:	33.8 us fl oz
Sheen:	mat
Stability:	do not freeze
Shelf Life:	36 month
Flash Point:	N / A
Consumption:	2000-8000 sf/gal

For further details please refer to MSDS.

Note

Keep soaked rags, pads and other working material in closed containers. Oil/wax in connection with sanding dust, cloth rags and the like must be moistened with water or deposited in a closed can or be disposed of in a safe way – danger of auto-ignition. The product itself is not auto-ignitive! Please refer to our Technical Special information Nr. 17! To increase the mechanical and chemical resistance and to inhibit drying, Brilliance OilCare can be mixed with Classic Plus in a ratio of 10:1.

Initial and basic care

Shake well prior to use. Before applying BRILLIANCE OILCARE the surface is cleaned with a damp rag (not a wet rag). The surface to clean must be clean and dry, maybe a basic maintenance is needed (refer to basic cleaning).

Apply BRILLIANCE OILCARE thinly and sparsely, and right after that polish the surface with a soft white pad or a lint-free cloth. When doing bigger surfaces, it has proven well to use a one-disc machine. Do go into the unsaturated area with the saturated pad to ensure that the pad will take up further polish. pad-polishing results in a satin-gloss to satin-matt surface. After about 30 min. the surface should be re-polished with an absorptive cloth in order to take up excessive oil that was not able to enter the wood. The polish shall not be allowed to form coats! It is recommended to ventilate well during or after working with

BRILLIANCE OILCARE so as to remove the solvents contained in the room's air.

The quantity of BRILLIANCE OILCARE must be small enough for the rotating pad not to splatter it. If this is the case, too much material, for sure, has been applied.

The basic maintenance is done from time to time manually or with a machine by using our BRILLIANCE CLEANER L91 KH-Verdünnung (thinner) or with BRILLIANCE BIOSOAP. This is needed when the floor does not look nice any more, and neither the routine care (intermediate cleaning) nor the basic care with BRILLIANCE OILCARE bring about an optical success.

In case prior to the application of BRILLIANCE OILCARE another care product such as BRILLIANCE AQUASATINPOLISH or BRILLIANCE FITPOLISH were used, so a basic cleaning is needed too.

The intermediate cleaning is done in order to remove small, water-soluble dirt or as a hygienic intermediate cleaning by hand or with a machine with a moist-damp rag using BRILLIANCE NEUTRALCLEANER or BRILLIANCE BIOSOAP.

Drying

Can be cautiously walked on after approx. 12 h at 73,4°F/50% rel. humidity.

Consumption

Depending on surface and way of work:
approx. 0.01-0.06 us fl oz/sq ft or approx. (2000-8000 sf/gal)

Do not apply excess oil!

Storage / transport

Shelf life of original unopened packing 36 months min. provided that material is transported and stored at a cool and dry place.

Use limitation

Floor with open, wide joints should not be treated with BRILLIANCE OILCARE because too much material is trowelled into the joints.

Safety Precautions

May cause skin and eye irritation. May be harmful if swallowed. May cause an allergic reaction. Avoid skin or eye contact and inhalation of vapors. Use with adequate ventilation. Wash thoroughly after handling. Keep unmixed containers closed. Do not seal containers containing mixed product due to release of carbon dioxide.

Do not use for sputtering or spraying. Keep out of reach of children. Residual quantities should not be poured into sewage water drains, but disposed of in compliance with local, state, and federal regulations.

BRILLIANCE OILCARE

Description of first aid measures

If medical advice is needed, have product container or label at hand.

24-hour emergency number in side USA: +1 872 5888271

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

Manufacturer's Recommendations

This Technical Data Sheet is based on extensive research and wide-ranging experience and is meant to assist you. Restrictive information and precautions have not been avoided in order to reduce risk of fault. Technical Data Sheets do not contain all applications or events that could occur with different species of wood, installation, techniques and finishing. Therefore, you cannot be released from the obligation to contact the manufacturer in cases of doubt, to make your own tests on site and to be critically attentive during the job process. The contents of this data sheet are not legally binding and do not establish any contractual legal relationship. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. This information is subject to change without further notice. Please read the instructions carefully before processing this product. This Berger-Seidle product must be

processed by a qualified person for parquet laying, for whom this manual is intended. The activities shall be carried out in accordance with the rules of the craft, the state of the art and the applicable standards and regulations of the country in which the product is used (USA/CAN = NWFA // AUS = ATFA). The specifications of DIN 18356 "Parquet and wood paving" and DIN 18365 "Flooring work", information sheets and technical information of the TKB, the BEB, the CTA and the BVPF-Bundesverband Parkett & Fußboden-technik must be observed. The customer must be informed about the cleaning and care specifications of the product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

References

The following sections of our information pages are integral parts of this information sheet:

- General information about how to use parquet sealing products
- Cleaning and care of the sealed/oiled floor
- Labelling and safety information (safety data sheet)

* If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are made.